SAFETY DATA SHEET

INTERFINE 2700/979 PART B FAST

Section 1. Identification

GHS product identifier : INTERFINE 2700/979 PART B FAST

SDS code : SYA056

Relevant identified uses of the substance or mixture and uses advised against

Identified uses
Professional use Industrial use

Uses advised against
Consumer use

Product use : Two component solvent borne coating for exterior use.

Supplier's details

Akzo Nobel Coatings
International Paint LLC
6001 Antoine Drive
Houston, Texas 77091
International Paint 1-800-589-1267
International Paint (International) 1-713-682-1711

Akzo Nobel Coatings Ltd.
110 Woodbine Downs Blvd.
Unit #4 Etobicoke, Ontario
Canada M9W 5S6
International Paint (International) 1-713-682-1711

Cía. Mexicana de Pinturas International, S.A. de C.V.
Carretera Anillo Periférico, No Ext 205,
No Interior A, Colonia HDA S JOSE, Garcia
Garcia, CP 66000, Nuevo Leon.

Emergency telephone number (with hours of operation) : CHEMTREC (USA) +1 (800) 424-9300 (24Hr)
CHEMTREC (International) +1 (703) 527-3887
Domestic Poison Control Center Customer Service +1 (800) 854-6813

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : ACUTE TOXICITY (oral) - Category 4
SKIN CORROSION - Category 1B
SERIOUS EYE DAMAGE - Category 1
SKIN SENSITIZATION - Category 1
GERM CELL MUTAGENICITY - Category 2
CARCINOGENICITY - Category 1A
TOXIC TO REPRODUCTION - Category 1B
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

Section 2. Hazards identification

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : Harmful if swallowed.
Causes severe skin burns and eye damage.
May cause an allergic skin reaction.
Suspected of causing genetic defects.
May cause cancer.
May damage fertility or the unborn child.
Causes damage to organs.
Causes damage to organs through prolonged or repeated exposure. (immune system)

Precautionary statements

Prevention : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

Response : IF exposed: Call a POISON CENTER or doctor. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

Storage : Store locked up.

Disposal : Dispose of contents and container in accordance with all local, regional, national or international regulations.

Hazards not otherwise classified : None known.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	%	CAS number
3-aminopropyltriethoxysilane	≥50 - ≤75	919-30-2
3-(trimethoxysilyl)propylamine	≥10 - ≤25	13822-56-5
dibutyltin di(acetate)	<5	1067-33-0
ethanol	<1	64-17-5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Section 3. Composition/information on ingredients

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses if easy to do. Chemical burns must be treated promptly by a physician.

Inhalation : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact : Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if irritation occurs.

Ingestion : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : Causes damage to organs following a single exposure if inhaled.

Skin contact : Causes severe burns. Causes damage to organs following a single exposure in contact with skin. May cause an allergic skin reaction.

Ingestion : Harmful if swallowed. Causes damage to organs following a single exposure if swallowed.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:
pain
watering
redness

Inhalation : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations

Section 4. First aid measures

Skin contact : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
reduced fetal weight
increase in fetal deaths
skeletal malformations

Ingestion : Adverse symptoms may include the following:
stomach pains
reduced fetal weight
increase in fetal deaths
skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media : Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media : None known.

Specific hazards arising from the chemical : In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
metal oxide/oxides

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
3-aminopropyltriethoxysilane 3-(trimethoxysilyl)propylamine dibutyltin di(acetate)	None. None. **ACGIH TLV (United States, 1/2023). [Tin, organic compounds] Absorbed through skin** TWA: 0.1 mg/m³, (as Sn) 8 hours. STEL: 0.2 mg/m³, (as Sn) 15 minutes. **NIOSH REL (United States, 10/2020). [tin organic compounds] Absorbed through skin** TWA: 0.1 mg/m³, (as Sn) 10 hours. **OSHA PEL (United States, 5/2018). [Tin, organic compounds]** TWA: 0.1 mg/m³, (as Sn) 8 hours. **OSHA PEL 1989 (United States, 3/1989). [Tin, organic compounds (as Sn)] Absorbed through skin** TWA: 0.1 mg/m³, (measured as Sn) 8 hours. Form: Organic
ethanol	**ACGIH TLV (United States, 1/2023).** STEL: 1000 ppm 15 minutes. **OSHA PEL 1989 (United States, 3/1989).** TWA: 1000 ppm 8 hours. TWA: 1900 mg/m³ 8 hours. **NIOSH REL (United States, 10/2020).** TWA: 1000 ppm 10 hours. TWA: 1900 mg/m³ 10 hours. **OSHA PEL (United States, 5/2018).** TWA: 1000 ppm 8 hours. TWA: 1900 mg/m³ 8 hours.

Appropriate engineering controls : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Section 8. Exposure controls/personal protection

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Wear a respirator conforming to EN140 with type A/P2 filter or better. Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state : Liquid.

Color : Colorless.

Odor : Solvent.

Odor threshold : Not available.

pH : Not applicable. [DIN EN 1262]

Melting point/freezing point : Not available.

Boiling point, initial boiling point, and boiling range : 194°C (381.2°F)

Flash point : Closed cup: 98°C (208.4°F) [Pensky-Martens]

Flammability : Not available.

Vapor pressure :

	Vapor Pressure at 20˚C			Vapor pressure at 50˚C		
Ingredient name	**mm Hg**	**kPa**	**Method**	**mm Hg**	**kPa**	**Method**
3-(trimethoxysilyl)propylamine	0.14	0.019				
dibutyltin di(acetate)	0.0024	0.00032	EU A.4			

Relative vapor density : Not available.

Section 9. Physical and chemical properties and safety characteristics

Density : 0.98 g/cm³ [DIN EN ISO 2811-1]

Solubility(ies) :

Media	Result
cold water	Not soluble [OECD (TG 105)]

Partition coefficient: n-octanol/water : Not applicable.

Auto-ignition temperature :

Ingredient name	°C	°F	Method
3-(trimethoxysilyl)propylamine	295	563	DIN 51794
dibutyltin di(acetate)	520	968	BS 14522

Decomposition temperature : Not available.

Viscosity : Kinematic (room temperature): 102 mm^2/s (102 cSt) [DIN EN ISO 3219]
Kinematic (40°C (104°F)): 100 mm^2/s (100 cSt) [DIN EN ISO 3219]

Particle characteristics

Median particle size : Not applicable.

Percentage of particles with aerodynamic diameter ≤ 10 µm : 0

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

Incompatible materials : No specific data.

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Section 11. Toxicological information

Product/ingredient name	Result	Species	Dose	Exposure
3-aminopropyltriethoxysilane	LD50 Oral	Rat	1780 mg/kg	-
dibutyltin di(acetate)	LD50 Dermal	Rabbit	2318 mg/kg	-
	LD50 Intravenous	Mouse	18 mg/kg	-
	LD50 Oral	Mouse	46 mg/kg	-
	LD50 Oral	Rat	32 mg/kg	-
ethanol	LC50 Inhalation Gas.	Mouse	>40000 ppm	10 minutes
	LC50 Inhalation Gas.	Mouse	>60000 ppm	1 hours
	LC50 Inhalation Gas.	Rat	20000 ppm	10 hours
	LC50 Inhalation Vapor	Mouse	39000 mg/m³	4 hours
	LC50 Inhalation Vapor	Rat	124700 mg/m³	4 hours
	LC50 Inhalation Vapor	Rat	5900 mg/m³	6 hours
	LD50 Intra-arterial	Rat	11 mg/kg	-
	LD50 Intraperitoneal	Guinea pig	3414 mg/kg	-
	LD50 Intraperitoneal	Mouse	4 mL/kg	-
	LD50 Intraperitoneal	Mouse	528 mg/kg	-
	LD50 Intraperitoneal	Rabbit	963 mg/kg	-
	LD50 Intraperitoneal	Rat	3600 µg/kg	-
	LD50 Intravenous	Mouse	2.8 mL/kg	-
	LD50 Intravenous	Mouse	1973 mg/kg	-
	LD50 Intravenous	Rabbit	2374 mg/kg	-
	LD50 Intravenous	Rat	1440 mg/kg	-
	LD50 Oral	Guinea pig	5560 mg/kg	-
	LD50 Oral	Mouse	10.5 mL/kg	-
	LD50 Oral	Mouse	3450 mg/kg	-
	LD50 Oral	Rabbit	6300 mg/kg	-
	LD50 Oral	Rat	7 g/kg	-
	LD50 Oral	Rat	15010 mg/kg	-
	LD50 Oral	Rat	7060 mg/kg	-
	LD50 Subcutaneous	Mouse	8285 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
3-aminopropyltriethoxysilane	Eyes - Mild irritant	Rabbit	-	100 mg	-
	Eyes - Severe irritant	Rabbit	-	24 hours 750 ug	-
	Skin - Severe irritant	Rabbit	-	24 hours 5 mg	-
dibutyltin di(acetate)	Skin - Severe irritant	Rabbit	-	30 minutes 500 mg	-
ethanol	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Eyes - Moderate irritant	Rabbit	-	100 Ul	-
	Eyes - Moderate irritant	Rabbit	-	0.066666667 minutes 100 mg	-
	Eyes - Severe irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Rabbit	-	400 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 mg	-

Sensitization

Product/ingredient name	Route of exposure	Species	Result
3-aminopropyltriethoxysilane	skin	Guinea pig	Sensitizing

Section 11. Toxicological information

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
ethanol	-	1	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
dibutyltin di(acetate)	Category 1	oral	-

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
dibutyltin di(acetate)	Category 1	-	immune system

Aspiration hazard

Not available.

Information on the likely routes of exposure : Not available.

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : Causes damage to organs following a single exposure if inhaled.

Skin contact : Causes severe burns. Causes damage to organs following a single exposure in contact with skin. May cause an allergic skin reaction.

Ingestion : Harmful if swallowed. Causes damage to organs following a single exposure if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:
pain
watering
redness

Inhalation : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations

Section 11. Toxicological information

Skin contact : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
reduced fetal weight
increase in fetal deaths
skeletal malformations

Ingestion : Adverse symptoms may include the following:
stomach pains
reduced fetal weight
increase in fetal deaths
skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : Causes damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : May cause cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : Suspected of causing genetic defects.

Reproductive toxicity : May damage fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Product as-supplied	717.4	N/A	N/A	N/A	N/A
3-aminopropyltriethoxysilane	500	N/A	N/A	N/A	N/A

Section 12. Ecological information

Toxicity

Section 12. Ecological information

Product/ingredient name	Result	Species	Exposure
dibutyltin di(acetate)	Acute EC50 35 µg/l Marine water	Algae - Skeletonema costatum - Exponential growth phase	72 hours
	Acute EC50 304 µg/l Marine water	Algae - Skeletonema costatum - Exponential growth phase	72 hours
	Acute EC50 127 µg/l Marine water	Algae - Thalassiosira pseudonana - Exponential growth phase	72 hours
ethanol	Acute EC50 17.921 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 1074 mg/l Fresh water	Crustaceans - Cypris subglobosa	48 hours
	Acute EC50 7640 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 2000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 12.9 g/L Fresh water	Fish - Pimephales promelas	96 hours
	Acute EC50 12800 mg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute LC50 25500 µg/l Marine water	Crustaceans - Artemia franciscana - Larvae	48 hours
	Acute LC50 5577000 µg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 3715000 µg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 6076000 µg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 5680 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 9268000 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 9248000 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 11000000 µg/l Marine water	Fish - Alburnus alburnus	96 hours
	Acute LC50 42000 µg/l Fresh water	Fish - Oncorhynchus mykiss	4 days
	Acute LC50 12720 ppm Fresh water	Fish - Pimephales promelas	96 hours
	Chronic NOEC 14 ppm Fresh water	Algae - Eutreptiella sp.	96 hours
	Chronic NOEC 350 ppm Fresh water	Algae - Heterosigma akashiwo	96 hours
	Chronic NOEC 50 ul/L Marine water	Algae - Hormosira banksii - Gamete	72 hours
	Chronic NOEC 20 ppm Fresh water	Algae - Prorocentrum minimum	96 hours
	Chronic NOEC 4.995 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 100 ul/L Fresh water	Daphnia - Daphnia magna - Neonate	21 days
	Chronic NOEC 100 ul/L Fresh water	Daphnia - Daphnia magna - Neonate	21 days
	Chronic NOEC 0.375 ul/L Fresh water	Fish - Gambusia holbrooki - Larvae	12 weeks

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	$LogP_{ow}$	BCF	Potential
3-aminopropyltriethoxysilane	1.7	3.4	Low
3-(trimethoxysilyl)propylamine	0.2	-	Low
ethanol	-0.35	-	Low

Mobility in soil

Section 12. Ecological information

Soil/Water partition coefficient : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

The information provided in section 14 is based on a bulk package shipment via ground transport in North America. All shippers are responsible for ensuring the proper transportation classification and package/container requirements are followed for the relevant mode of transport.

	DOT Classification	IMDG	IATA
UN number	UN3066	UN3066	UN3066
UN proper shipping name	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL
Transport hazard class(es)	8 	8 	8 
Packing group	II	II	II
Environmental hazards	No.	Marine Pollutant(s): dibutyltin di(acetate)	Yes. The environmentally hazardous substance mark is not required.

Additional information

IMDG : **Emergency schedules** F-A, S-B
The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.

IATA : The environmentally hazardous substance mark may appear if required by other transportation regulations.

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not available.

Section 15. Regulatory information

U.S. Federal regulations : **TSCA 5(a)2 final significant new use rules:** No products found.
TSCA 5(e) substance consent order: No products found.
TSCA 8(a) CDR Exempt/Partial exemption: Not determined
United States inventory (TSCA 8b): All components are active or exempted.
Clean Water Act (CWA) 307: toluene; lead powder
Clean Water Act (CWA) 311: acetic acid; toluene

Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs) : Listed

Clean Air Act Section 602 Class I Substances : Not listed

Clean Air Act Section 602 Class II Substances : Not listed

DEA List I Chemicals (Precursor Chemicals) : Not listed

DEA List II Chemicals (Essential Chemicals) : Not listed

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : ACUTE TOXICITY (oral) - Category 4
SKIN CORROSION - Category 1B
SERIOUS EYE DAMAGE - Category 1
SKIN SENSITIZATION - Category 1
GERM CELL MUTAGENICITY - Category 2
CARCINOGENICITY - Category 1A
TOXIC TO REPRODUCTION - Category 1B
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

Composition/information on ingredients

Name	%	Classification
3-aminopropyltriethoxysilane	≥50 - ≤75	ACUTE TOXICITY (oral) - Category 4 SKIN CORROSION - Category 1B SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1
3-(trimethoxysilyl)propylamine	≥10 - ≤25	SKIN IRRITATION - Category 2 SERIOUS EYE DAMAGE - Category 1
dibutyltin di(acetate)	<5	SKIN CORROSION - Category 1 SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1 GERM CELL MUTAGENICITY - Category 2 TOXIC TO REPRODUCTION - Category 1B SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
ethanol	<1	FLAMMABLE LIQUIDS - Category 2 EYE IRRITATION - Category 2A

Section 15. Regulatory information

		CARCINOGENICITY - Category 1A

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	lead powder	7439-92-1	<0.03
Supplier notification	lead powder	7439-92-1	<0.03

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts : The following components are listed: DIBUTYLTIN DIACETATE

New York : None of the components are listed.

New Jersey : The following components are listed: ETHYL ALCOHOL

Pennsylvania : None of the components are listed.

California Prop. 65

⚠ **WARNING**: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level	Type of toxicity
toluene methanol lead powder	- - Yes.	Yes. Yes. Yes.	Developmental Developmental Cancer, Developmental, Reproductive female, Reproductive male

Inventory list

Australia : All components are listed or exempted.

Canada : At least one component is not listed in DSL but all such components are listed in NDSL.

China : All components are listed or exempted.

Eurasian Economic Union : **Russian Federation inventory**: All components are listed or exempted.

Japan : **Japan inventory (CSCL)**: Not determined.
Japan inventory (ISHL): Not determined.

New Zealand : All components are listed or exempted.

Philippines : All components are listed or exempted.

Republic of Korea : All components are listed or exempted.

Taiwan : All components are listed or exempted.

Thailand : All components are listed or exempted.

Turkey : Not determined.

United States : All components are active or exempted.

Viet Nam : All components are listed or exempted.

Section 16. Other information

Procedure used to derive the classification

Classification	Justification
ACUTE TOXICITY (oral) - Category 4	Calculation method
SKIN CORROSION - Category 1B	Calculation method
SERIOUS EYE DAMAGE - Category 1	Calculation method
SKIN SENSITIZATION - Category 1	Calculation method
GERM CELL MUTAGENICITY - Category 2	Calculation method
CARCINOGENICITY - Category 1A	Calculation method
TOXIC TO REPRODUCTION - Category 1B	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1	Calculation method

History

Date of printing : 1/19/2026

Date of issue/ Date of revision : 1/19/2026

Date of previous issue : 6/25/2025

Version : 5

Unique ID : 7E46AA28D30B1EDF8FDEB2A9821BC867

Key to abbreviations : ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
N/A = Not available
SGG = Segregation Group
UN = United Nations

Indicates information that has changed from previously issued version.

Notice to reader

IMPORTANT NOTE: the information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates.

Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Unless we have agreed to the contrary, all products are supplied by us subject to our standard terms and conditions of business, which include limitations of liability. Please make sure to refer to these and / or the relevant agreement which you have with AkzoNobel (or its affiliate, as the case may be).
© AkzoNobel