SAFETY DATA SHEET

INTERPRIME 198 WHITE

Section 1. Identification

Product identifier : INTERPRIME 198 WHITE

SDS code : CPA097

Relevant identified uses of the substance or mixture and uses advised against

Identified uses
Professional use Industrial use

Uses advised against
All other uses

Product use : Alkyd emulsion coating for exterior use.

Supplier's details

Akzo Nobel Coatings
International Paint LLC
6001 Antoine Drive
Houston, Texas 77091
International Paint 1-800-589-1267
International Paint (International) 1-713-682-1711

Akzo Nobel Coatings Ltd.
110 Woodbine Downs Blvd.
Unit #4 Etobicoke, Ontario
Canada M9W 5S6
International Paint (International) 1-713-682-1711

Emergency telephone number (with hours of operation) : CHEMTREC (USA) +1 (800) 424-9300 (24Hr)
CHEMTREC (International) +1 (703) 527-3887

Section 2. Hazard identification

Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 3
SKIN IRRITATION - Category 2
EYE IRRITATION - Category 2A
SKIN SENSITIZATION - Category 1
CARCINOGENICITY - Category 1
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3

GHS label elements

Section 2. Hazard identification

Hazard pictograms :



Signal word : Danger

Hazard statements : Flammable liquid and vapor.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause respiratory irritation.
May cause drowsiness or dizziness.
May cause cancer.

Precautionary statements

Prevention : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Avoid breathing vapor. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

Response : IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

Storage : Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

Disposal : Dispose of contents and container in accordance with all local, regional, national or international regulations.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Other means of identification : Not available.

Ingredient name	% (w/w)	CAS number
Solvent naphtha (petroleum), light arom.	≥10 - ≤30	64742-95-6
titanium dioxide	≥10 - ≤30	13463-67-7
1,2,4-trimethylbenzene	≥5 - ≤10	95-63-6
calcium phosphate	≥1 - ≤5	10103-46-5
xylene	≥1 - ≤5	1330-20-7
butan-1-ol	≥1 - ≤5	71-36-3
ethylbenzene	≥0.1 - ≤1	100-41-4
ethanol	≥0.1 - ≤1	64-17-5
cumene	≥0.1 - ≤1	98-82-8
2-butanone oxime	≥0.1 - ≤1	96-29-7

Section 3. Composition/information on ingredients

Ranges if listed above for hazardous ingredient(s) are prescribed ranges. The actual concentration(s) or actual concentration range(s) are being withheld as a trade secret.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-aid measures

Description of necessary first aid measures

Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses if easy to do. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.

Skin contact : Causes skin irritation. May cause an allergic skin reaction.

Ingestion : Can cause central nervous system (CNS) depression.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:
pain or irritation
watering
redness

Inhalation : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness

Section 4. First-aid measures

Skin contact : Adverse symptoms may include the following:
irritation
redness

Ingestion : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media : Use dry chemical, CO_2, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

Specific hazards arising from the chemical : Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
sulfur oxides
phosphorus oxides
metal oxide/oxides

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Section 6. Accidental release measures

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
titanium dioxide	**CA British Columbia Provincial (Canada, 6/2023). [Titanium dioxide] Notes: The 8-hour TWA listed in the Table is for the total dust. The substance also has an 8-hour TWA of 3 mg/m3 for the respirable fraction.** TWA: 10 mg/m³ 8 hours. Form: Total dust TWA: 3 mg/m³ 8 hours. Form: respirable fraction **CA Quebec Provincial (Canada, 6/2022).** TWAEV: 10 mg/m³ 8 hours. Form: Total dust. **CA Alberta Provincial (Canada, 6/2018). Skin sensitizer.** OEL: 10 mg/m³ 8 hours. **CA Saskatchewan Provincial (Canada, 7/2013).** STEL: 20 mg/m³ 15 minutes. TWA: 10 mg/m³ 8 hours. **CA Ontario Provincial (Canada, 6/2019).** TWA: 10 mg/m³ 8 hours. Form: total dust
1,2,4-trimethylbenzene	**CA Alberta Provincial (Canada, 6/2018). [Trimethyl benzene]** OEL: 123 mg/m³ 8 hours. OEL: 25 ppm 8 hours. **CA British Columbia Provincial (Canada, 6/2023). [Trimethyl benzene (mixed isomers)]** TWA: 25 ppm 8 hours. **CA Quebec Provincial (Canada, 6/2022). [Trimethyl benzene] Skin sensitizer. Inhalation sensitizer.** TWAEV: 25 ppm 8 hours. **CA Ontario Provincial (Canada, 6/2019). [Trimethyl benzene (mixed isomers)]** TWA: 25 ppm 8 hours. **CA Saskatchewan Provincial (Canada, 7/2013). [Trimethyl benzene]** STEL: 30 ppm 15 minutes. TWA: 25 ppm 8 hours.
xylene	**CA Alberta Provincial (Canada, 6/2018). [Dimethylbenzene]** OEL: 651 mg/m³ 15 minutes. OEL: 150 ppm 15 minutes. OEL: 434 mg/m³ 8 hours. OEL: 100 ppm 8 hours. **CA British Columbia Provincial (Canada, 6/2023). [Xylene (o, m & p isomers)]** STEL: 150 ppm 15 minutes. TWA: 100 ppm 8 hours. **CA Quebec Provincial (Canada, 6/2022). [Xylene]** STEV: 651 mg/m³ 15 minutes. STEV: 150 ppm 15 minutes. TWAEV: 434 mg/m³ 8 hours.

Section 8. Exposure controls/personal protection

	TWAEV: 100 ppm 8 hours. **CA Ontario Provincial (Canada, 6/2019). [Xylene (o-, m-, p-isomers)]** STEL: 150 ppm 15 minutes. TWA: 100 ppm 8 hours. **CA Saskatchewan Provincial (Canada, 7/2013). [Xylene]** STEL: 150 ppm 15 minutes. TWA: 100 ppm 8 hours.
butan-1-ol	**CA British Columbia Provincial (Canada, 6/2023).** C: 30 ppm 15 minutes. TWA: 15 ppm 8 hours. **CA Ontario Provincial (Canada, 6/2019).** TWA: 20 ppm 8 hours. **CA Quebec Provincial (Canada, 6/2022). Absorbed through skin.** STEV: 152 mg/m³ 15 minutes. STEV: 50 ppm 15 minutes. **CA Alberta Provincial (Canada, 6/2018). Skin sensitizer.** OEL: 60 mg/m³ 8 hours. OEL: 20 ppm 8 hours. **CA Saskatchewan Provincial (Canada, 7/2013).** STEL: 30 ppm 15 minutes. TWA: 20 ppm 8 hours.
ethylbenzene	**CA Alberta Provincial (Canada, 6/2018).** OEL: 543 mg/m³ 15 minutes. OEL: 125 ppm 15 minutes. OEL: 434 mg/m³ 8 hours. OEL: 100 ppm 8 hours. **CA British Columbia Provincial (Canada, 6/2023).** TWA: 20 ppm 8 hours. **CA Ontario Provincial (Canada, 6/2019).** TWA: 20 ppm 8 hours. **CA Quebec Provincial (Canada, 6/2022).** TWAEV: 20 ppm 8 hours. **CA Saskatchewan Provincial (Canada, 7/2013).** STEL: 125 ppm 15 minutes. TWA: 100 ppm 8 hours.
ethanol	**CA Alberta Provincial (Canada, 6/2018).** OEL: 1880 mg/m³ 8 hours. OEL: 1000 ppm 8 hours. **CA British Columbia Provincial (Canada, 6/2023).** STEL: 1000 ppm 15 minutes. **CA Ontario Provincial (Canada, 6/2019).** STEL: 1000 ppm 15 minutes. **CA Saskatchewan Provincial (Canada, 7/2013).** STEL: 1250 ppm 15 minutes. TWA: 1000 ppm 8 hours. **CA Quebec Provincial (Canada, 6/2022).** STEV: 1000 ppm 15 minutes.
cumene	**CA Alberta Provincial (Canada, 6/2018).** OEL: 246 mg/m³ 8 hours. OEL: 50 ppm 8 hours.

Section 8. Exposure controls/personal protection

	CA British Columbia Provincial (Canada, 6/2023). STEL: 75 ppm 15 minutes. TWA: 25 ppm 8 hours. **CA Ontario Provincial (Canada, 6/2019). Absorbed through skin.** TWA: 50 ppm 8 hours. **CA Quebec Provincial (Canada, 6/2022).** TWAEV: 246 mg/m³ 8 hours. TWAEV: 50 ppm 8 hours. **CA Saskatchewan Provincial (Canada, 7/2013).** STEL: 74 ppm 15 minutes. TWA: 50 ppm 8 hours.
2-butanone oxime	**OARS WEEL (United States, 4/2022). Skin sensitizer.** TWA: 10 ppm 8 hours.

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Section 8. Exposure controls/personal protection

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Wear a respirator conforming to EN140 with type A/P2 filter or better.

Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state : Liquid.

Color : White.

Odor : Solvent.

Odor threshold : Not available.

pH : Not available. [DIN EN 1262]

Melting point/freezing point : Not available.

Boiling point, initial boiling point, and boiling range : 146°C (294.8°F)

Flash point : Closed cup: 35°C (95°F) [Pensky-Martens]

Flammability : Not available.

Lower and upper explosion limit : Greatest known range: Lower: 1.4% Upper: 11.3% (butan-1-ol)

Vapor pressure :

	Vapor Pressure at 20˚C			Vapor pressure at 50˚C		
Ingredient name	**mm Hg**	**kPa**	**Method**	**mm Hg**	**kPa**	**Method**
butan-1-ol	<7.50064	<1	DIN EN 13016-2			
xylene	6.7	0.89				
1,2,4-trimethylbenzene	2.25018	0.3				

Relative vapor density : Not available.

Density : 1.335 g/cm³ [DIN EN ISO 2811-1]

Solubility(ies) :

Media	Result
cold water	Not soluble [OECD (TG 105)]

Partition coefficient: n-octanol/water : Not applicable.

Auto-ignition temperature :

Ingredient name	°C	°F	Method
Solvent naphtha (petroleum), light arom.	280 to 470	536 to 878	
butan-1-ol	355	671	EU A.15
xylene	432	809.6	

Decomposition temperature : Not available.

Viscosity : Kinematic (room temperature): 155 mm^2/s (155 cSt) [DIN EN ISO 3219]
Kinematic (40°C (104°F)): 207 mm^2/s (207 cSt) [DIN EN ISO 3219]

Particle characteristics

Section 9. Physical and chemical properties and safety characteristics

Median particle size : Not applicable.

Percentage of particles with aerodynamic diameter ≤ 10 µm : 0

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

Incompatible materials : Reactive or incompatible with the following materials: oxidizing materials

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Solvent naphtha (petroleum), light arom.	LD50 Oral	Rat	8400 mg/kg	-
1,2,4-trimethylbenzene	LC50 Inhalation Vapor	Rat	18000 mg/m³	4 hours
	LD50 Oral	Rat	5 g/kg	-
xylene	LD50 Oral	Rat	4300 mg/kg	-
	LD50 Subcutaneous	Rat	1700 mg/kg	-
butan-1-ol	LC50 Inhalation Vapor	Rat	24000 mg/m³	4 hours
	LD50 Dermal	Rabbit	3400 mg/kg	-
	LD50 Oral	Rat	790 mg/kg	-
ethylbenzene	LC50 Inhalation Gas.	Rabbit	4000 ppm	4 hours
	LC50 Inhalation Vapor	Mouse	35500 mg/m³	2 hours
	LC50 Inhalation Vapor	Rat	55000 mg/m³	2 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Dermal	Rabbit	17800 uL/kg	-
	LD50 Intraperitoneal	Mouse	2624 uL/kg	-
	LD50 Oral	Rat	3500 mg/kg	-
	LD50 Oral	Rat	3500 mg/kg	-
ethanol	LC50 Inhalation Gas.	Mouse	>40000 ppm	10 minutes
	LC50 Inhalation Gas.	Mouse	>60000 ppm	1 hours
	LC50 Inhalation Gas.	Rat	20000 ppm	10 hours
	LC50 Inhalation Vapor	Mouse	39000 mg/m³	4 hours
	LC50 Inhalation Vapor	Rat	124700 mg/m³	4 hours
	LC50 Inhalation Vapor	Rat	5900 mg/m³	6 hours
	LD50 Intra-arterial	Rat	11 mg/kg	-
	LD50 Intraperitoneal	Guinea pig	3414 mg/kg	-
	LD50 Intraperitoneal	Mouse	4 mL/kg	-
	LD50 Intraperitoneal	Mouse	528 mg/kg	-
	LD50 Intraperitoneal	Rabbit	963 mg/kg	-

Section 11. Toxicological information

	LD50 Intraperitoneal	Rat	3600 µg/kg	-
	LD50 Intravenous	Mouse	2.8 mL/kg	-
	LD50 Intravenous	Mouse	1973 mg/kg	-
	LD50 Intravenous	Rabbit	2374 mg/kg	-
	LD50 Intravenous	Rat	1440 mg/kg	-
	LD50 Oral	Guinea pig	5560 mg/kg	-
	LD50 Oral	Mouse	10.5 mL/kg	-
	LD50 Oral	Mouse	3450 mg/kg	-
	LD50 Oral	Rabbit	6300 mg/kg	-
	LD50 Oral	Rat	7 g/kg	-
	LD50 Oral	Rat	15010 mg/kg	-
	LD50 Oral	Rat	7060 mg/kg	-
	LD50 Subcutaneous	Mouse	8285 mg/kg	-
cumene	LC50 Inhalation Vapor	Mouse	15300 mg/m³	2 hours
	LC50 Inhalation Vapor	Mouse	10 g/m³	7 hours
	LC50 Inhalation Vapor	Mouse	10000 mg/m³	7 hours
	LC50 Inhalation Vapor	Rat	39000 mg/m³	4 hours
	LD50 Dermal	Rabbit	12300 uL/kg	-
	LD50 Oral	Mouse	12750 mg/kg	-
	LD50 Oral	Rat	2.9 g/kg	-
2-butanone oxime	LD50 Dermal	Rabbit	200 uL/kg	-
	LD50 Intraperitoneal	Mouse	200 mg/kg	-
	LD50 Oral	Mouse	1 g/kg	-
	LD50 Oral	Rat	930 mg/kg	-
	LD50 Subcutaneous	Mouse	2700 mg/kg	-
	LD50 Subcutaneous	Rat	2702 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Solvent naphtha (petroleum), light arom.	Eyes - Mild irritant	Rabbit	-	24 hours 100 Ul	-
xylene	Eyes - Mild irritant	Rabbit	-	87 mg	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 mg	-
	Skin - Mild irritant	Rat	-	8 hours 60 Ul	-
	Skin - Moderate irritant	Rabbit	-	100 %	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
butan-1-ol	Eyes - Severe irritant	Rabbit	-	0.005 Ml	-
	Eyes - Severe irritant	Rabbit	-	1.62 mg	-
	Eyes - Severe irritant	Rabbit	-	24 hours 2 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 mg	-
ethylbenzene	Eyes - Severe irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 15 mg	-
ethanol	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Eyes - Moderate irritant	Rabbit	-	100 Ul	-
	Eyes - Moderate irritant	Rabbit	-	0.066666667 minutes 100 mg	-
	Eyes - Severe irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Rabbit	-	400 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 mg	-
cumene	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Eyes - Mild irritant	Rabbit	-	86 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 10	-

Section 11. Toxicological information

	Skin - Moderate irritant	Rabbit	-	mg 24 hours 100 mg	-
2-butanone oxime	Eyes - Severe irritant	Rabbit	-	100 Ul	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	IARC	NTP	ACGIH
Solvent naphtha (petroleum), light arom.	-	-	A3
titanium dioxide	2B	-	A4
xylene	3	-	A4
ethylbenzene	2B	-	A3
ethanol	1	-	A3
cumene	2B	Reasonably anticipated to be a human carcinogen.	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Solvent naphtha (petroleum), light arom.	Category 3	-	Respiratory tract irritation
	Category 3		Narcotic effects
1,2,4-trimethylbenzene	Category 3	-	Respiratory tract irritation
calcium phosphate	Category 3	-	Respiratory tract irritation
xylene	Category 3	-	Respiratory tract irritation
butan-1-ol	Category 3	-	Respiratory tract irritation
	Category 3		Narcotic effects
cumene	Category 3	-	Respiratory tract irritation
2-butanone oxime	Category 1	-	upper respiratory tract
	Category 3		Narcotic effects

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
ethylbenzene	Category 2	-	hearing organs
2-butanone oxime	Category 2	-	blood system

Aspiration hazard

Section 11. Toxicological information

Name	Result
Solvent naphtha (petroleum), light arom.	ASPIRATION HAZARD - Category 1
xylene	ASPIRATION HAZARD - Category 1
ethylbenzene	ASPIRATION HAZARD - Category 1
cumene	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure : Not available.

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.

Skin contact : Causes skin irritation. May cause an allergic skin reaction.

Ingestion : Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:
pain or irritation
watering
redness

Inhalation : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness

Skin contact : Adverse symptoms may include the following:
irritation
redness

Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : May cause cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

Numerical measures of toxicity

Section 11. Toxicological information

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Product as-supplied	15494.1	25418.4	N/A	102.3	N/A
1,2,4-trimethylbenzene	5000	N/A	N/A	18	N/A
xylene	N/A	1100	N/A	11	N/A
butan-1-ol	500	N/A	N/A	N/A	N/A
ethylbenzene	N/A	N/A	N/A	11	N/A
2-butanone oxime	100	1100	N/A	N/A	N/A

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute LC50 >1000 mg/l Fresh water	Fish - Pimephales promelas	96 hours
1,2,4-trimethylbenzene	Acute LC50 17000 µg/l Marine water	Crustaceans - Cancer magister - Zoea	48 hours
	Acute LC50 4910 µg/l Marine water	Crustaceans - Elasmopus pectenicrus - Adult	48 hours
	Acute LC50 7720 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute LC50 22.4 mg/l Fresh water	Fish - Tilapia zillii	96 hours
xylene	Acute EC50 90 mg/l Fresh water	Crustaceans - Cypris subglobosa	48 hours
	Acute LC50 8.5 ppm Marine water	Crustaceans - Palaemonetes pugio - Adult	48 hours
	Acute LC50 8500 µg/l Marine water	Crustaceans - Palaemonetes pugio	48 hours
	Acute LC50 16940 µg/l Fresh water	Fish - Carassius auratus	96 hours
	Acute LC50 15700 µg/l Fresh water	Fish - Lepomis macrochirus - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Acute LC50 20870 µg/l Fresh water	Fish - Lepomis macrochirus	96 hours
	Acute LC50 19000 µg/l Fresh water	Fish - Lepomis macrochirus	96 hours
	Acute LC50 13400 µg/l Fresh water	Fish - Pimephales promelas	96 hours
butan-1-ol	Acute EC50 1983 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 2300000 µg/l Marine water	Fish - Alburnus alburnus	96 hours
	Acute LC50 1910000 µg/l Fresh water	Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Acute LC50 1940000 µg/l Fresh water	Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Acute LC50 1730000 µg/l Fresh water	Fish - Pimephales promelas	96 hours
ethylbenzene	Acute EC50 4600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 5400 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 3600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Acute EC50 4900 µg/l Marine water	Algae - Skeletonema costatum	72 hours
	Acute EC50 7700 µg/l Marine water	Algae - Skeletonema costatum	96 hours
	Acute EC50 6.53 mg/l Marine water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute EC50 13.3 mg/l Marine water	Crustaceans - Artemia sp. - Nauplii	48 hours

Section 12. Ecological information

	Acute EC50 2.97 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute EC50 2.93 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 8.78 mg/l Marine water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute LC50 13.3 mg/l Marine water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute LC50 40000 µg/l Marine water	Crustaceans - Cancer magister - Zoea	48 hours
	Acute LC50 18.4 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 13.9 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 75000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 5100 µg/l Marine water	Fish - Menidia menidia	96 hours
	Acute LC50 4.3 ul/L Marine water	Fish - Morone saxatilis - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Acute LC50 4200 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 9090 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute LC50 9100 µg/l Fresh water	Fish - Pimephales promelas	96 hours
ethanol	Acute EC50 17.921 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 1074 mg/l Fresh water	Crustaceans - Cypris subglobosa	48 hours
	Acute EC50 7640 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 2000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 12.9 g/L Fresh water	Fish - Pimephales promelas	96 hours
	Acute EC50 12800 mg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute LC50 25500 µg/l Marine water	Crustaceans - Artemia franciscana - Larvae	48 hours
	Acute LC50 5577000 µg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 3715000 µg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 6076000 µg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 5680 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 9268000 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 9248000 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 11000000 µg/l Marine water	Fish - Alburnus alburnus	96 hours
	Acute LC50 42000 µg/l Fresh water	Fish - Oncorhynchus mykiss	4 days
	Acute LC50 12720 ppm Fresh water	Fish - Pimephales promelas	96 hours
	Chronic NOEC 14 ppm Fresh water	Algae - Eutreptiella sp.	96 hours
	Chronic NOEC 350 ppm Fresh water	Algae - Heterosigma akashiwo	96 hours
	Chronic NOEC 50 ul/L Marine water	Algae - Hormosira banksii - Gamete	72 hours
	Chronic NOEC 20 ppm Fresh water	Algae - Prorocentrum minimum	96 hours
	Chronic NOEC 4.995 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 100 ul/L Fresh water	Daphnia - Daphnia magna - Neonate	21 days
	Chronic NOEC 100 ul/L Fresh water	Daphnia - Daphnia magna - Neonate	21 days
	Chronic NOEC 0.375 ul/L Fresh water	Fish - Gambusia holbrooki - Larvae	12 weeks
cumene	Acute EC50 7.4 mg/l Marine water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute EC50 7.5 mg/l Marine water	Crustaceans - Artemia sp. -	48 hours

Section 12. Ecological information

		Nauplii	
	Acute EC50 10.6 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute EC50 10.6 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute EC50 11.2 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 7.4 mg/l Marine water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute LC50 8 mg/l Marine water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute LC50 20.3 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 20.3 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 2700 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 6320 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute LC50 5100 µg/l Fresh water	Fish - Poecilia reticulata	96 hours
2-butanone oxime	Acute LC50 843000 µg/l Fresh water	Fish - Pimephales promelas	96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	$LogP_{ow}$	BCF	Potential
Solvent naphtha (petroleum), light arom.	-	10 to 2500	high
1,2,4-trimethylbenzene	3.63	243	low
xylene	3.12	8.1 to 25.9	low
butan-1-ol	1	-	low
ethylbenzene	3.6	-	low
ethanol	-0.35	-	low
cumene	3.55	35.48	low
2-butanone oxime	0.63	2.5 to 5.8	low

Mobility in soil

Soil/water partition coefficient (K_{OC}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

The information provided in section 14 is based on a bulk package shipment via ground transport in North America. All shippers are responsible for ensuring the proper transportation classification and package/container requirements are followed for the relevant mode of transport.

	TDG Classification	IMDG	IATA
UN number	UN1263	UN1263	UN1263
UN proper shipping name	PAINT	PAINT	PAINT
Transport hazard class(es)	3 	3 	3 
Packing group	III	III	III
Environmental hazards	Yes.	Marine Pollutant(s): Solvent naphtha (petroleum), light arom., 1,2,4-trimethylbenzene	Yes. The environmentally hazardous substance mark is not required.

Additional information

TDG Classification : Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3), 2.7 (Marine pollutant mark).
The marine pollutant mark is not required when transported by road or rail.

IMDG : **Emergency schedules** F-E, _S-E_
The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.

IATA : The environmentally hazardous substance mark may appear if required by other transportation regulations.

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not available.

Section 15. Regulatory information

Canadian lists

Canadian NPRI : The following components are listed: light aromatic solvent naphtha; light aromatic solvent naphtha; 1,2,4-trimethylbenzene; phosphorus (total); xylene (all isomers); n-butyl alcohol

CEPA Toxic substances : None of the components are listed.

Inventory list

Canada : At least one component is not listed in DSL but all such components are listed in NDSL.

United States : Not determined.

Section 16. Other information

History

Date of printing	:	8/13/2024
Date of issue/ Date of revision	:	8/13/2024
Date of previous issue	:	7/25/2023
Version	:	2
Unique ID	:	7E46AA28D30B1EDF96AE5693D0994C00

Key to abbreviations : ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
HPR = Hazardous Products Regulations
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
N/A = Not available
SGG = Segregation Group
UN = United Nations

Procedure used to derive the classification

Classification	Justification
FLAMMABLE LIQUIDS - Category 3	On basis of test data
SKIN IRRITATION - Category 2	Calculation method
EYE IRRITATION - Category 2A	Calculation method
SKIN SENSITIZATION - Category 1	Calculation method
CARCINOGENICITY - Category 1	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3	Calculation method

Indicates information that has changed from previously issued version.

Notice to reader

IMPORTANT NOTE: the information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates.

Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Unless we have agreed to the contrary, all products are supplied by us subject to our standard terms and conditions of business, which include limitations of liability. Please make sure to refer to these and / or the relevant agreement which you have with AkzoNobel (or its affiliate, as the case may be).
© AkzoNobel